

FORM PTO-1390
(REV 12-29-99)

U.S. DEPARTMENT OF COMMERCE PATENT AND TRADEMARK OFFICE

ATTORNEY'S DOCKET NUMBER

TRANSMITTAL LETTER TO THE UNITED STATES
DESIGNATED/ELECTED OFFICE (DO/EO/US)
CONCERNING A FILING UNDER 35 U.S.C. 371FILED: JANUARY 12, 2001
566.39480X00

U.S. APPLICATION NO. (If known, see 37 CFR 1.5)

09/743631

INTERNATIONAL APPLICATION NO.

PCT/JP98/03178

INTERNATIONAL FILING DATE

15 July 1998 (15.07.98)

PRIORITY DATE CLAIMED

TITLE OF INVENTION METHOD OF SWITCHING BUSY LINES IN MOBILE COMMUNICATION NETWORK

APPLICANT(S) FOR DO/EO/US KUSAKI, Tsutomu, HIRAYAMA Koji, SHIRAI Keisuke,

Applicant herewith submits to the United States Designated/Elected Office (DO/EO/US) the following items and other information:

1. ☒ This is a **FIRST** submission of items concerning a filing under 35 U.S.C. 371.
2. ☐ This is a **SECOND** or **SUBSEQUENT** submission of items concerning a filing under 35 U.S.C. 371.
3. ☐ This express request to begin national examination procedures (35 U.S.C. 371(f)) at any time rather than delay examination until the expiration of the applicable time limit set in 35 U.S.C. 371(b) and PCT Articles 22 and 39(1).
4. ☒ A proper Demand for International Preliminary Examination was made by the 19th month from the earliest claimed priority date.
5. ☒ A copy of the International Application as filed (35 U.S.C. 371(c)(2))
 - a. ☐ is transmitted herewith (required only if not transmitted by the International Bureau).
 - b. ☒ has been transmitted by the International Bureau.
 - c. ☐ is not required, as the application was filed in the United States Receiving Office (RO/US).
6. ☒ A translation of the International Application into English (35 U.S.C. 371(c)(2)).
7. ☐ Amendments to the claims of the International Application under PCT Article 19 (35 U.S.C. 371(c)(3))
 - a. ☐ are transmitted herewith (required only if not transmitted by the International Bureau).
 - b. ☐ have been transmitted by the International Bureau.
 - c. ☐ have not been made; however, the time limit for making such amendments has NOT expired.
 - d. ☐ have not been made and will not be made.
8. ☐ A translation of the amendments to the claims under PCT Article 19 (35 U.S.C. 371(c)(3)).
9. ☒ An oath or declaration of the inventor(s) (35 U.S.C. 371(c)(4)).
10. ☐ A translation of the annexes to the International Preliminary Examination Report under PCT Article 36 (35 U.S.C. 371(c)(5)).

Items 11. to 16. below concern document(s) or information included:

11. ☐ An Information Disclosure Statement under 37 CFR 1.97 and 1.98.
12. ☒ An assignment document for recording. A separate cover sheet in compliance with 37 CFR 3.28 and 3.31 is included.
13. ☒ A FIRST preliminary amendment.
☐ A SECOND or SUBSEQUENT preliminary amendment.
14. ☐ A substitute specification.
15. ☒ A change of power of attorney and/or address letter.
16. ☒ Other items or information:

INTERNATIONAL PUBLICATION SHEET NO. WO00/04733
 INTERNATIONAL SEARCH REPORT
 INTERNATIONAL PRELIMINARY EXAMINATION REPORT
 PTO FORM 1449 W/REFS.
 FIGS. 1-9
 CREDIT CARD PAYMENT FORM

17. ☒ The following fees are submitted:**BASIC NATIONAL FEE (37 CFR 1.492 (a) (1) - (5)) :**

- ✓ Neither international preliminary examination fee (37 CFR 1.482) nor international search fee (37 CFR 1.445(a)(2)) paid to USPTO and International Search Report not prepared by the EPO or JPO \$970.00
- International preliminary examination fee (37 CFR 1.482) not paid to USPTO but International Search Report prepared by the EPO or JPO \$840.00
- International preliminary examination fee (37 CFR 1.482) not paid to USPTO but international search fee (37 CFR 1.445(a)(2)) paid to USPTO \$690.00
- International preliminary examination fee paid to USPTO (37 CFR 1.482) but all claims did not satisfy provisions of PCT Article 33(1)-(4) \$670.00
- International preliminary examination fee paid to USPTO (37 CFR 1.482) and all claims satisfied provisions of PCT Article 33(1)-(4) \$96.00

ENTER APPROPRIATE BASIC FEE AMOUNT =**CALCULATIONS PTO USE ONLY**

\$ 860.00

Surcharge of \$130.00 for furnishing the oath or declaration later than ☐ 20 ☐ 30 months from the earliest claimed priority date (37 CFR 1.492(e)).

\$ 0.00

CLAIMS	NUMBER FILED	NUMBER EXTRA	RATE		
Total claims	20 - 20 =	0	X \$18.00	\$	0.00
Independent claims	8 - 3 =	5	X \$78.00	\$	400.00
MULTIPLE DEPENDENT CLAIM(S) (if applicable)			+ \$260.00	\$	0.00

TOTAL OF ABOVE CALCULATIONS =

\$ 1,260.00

Reduction of 1/2 for filing by small entity, if applicable. A Small Entity Statement must also be filed (Note 37 CFR 1.9, 1.27, 1.28).

\$ 0.00

SUBTOTAL =

\$ 1,260.00

Processing fee of \$130.00 for furnishing the English translation later than ☐ 20 ☐ 30 months from the earliest claimed priority date (37 CFR 1.492(f)).

\$ 0.00

TOTAL NATIONAL FEE =

\$ 1,260.00

Fee for recording the enclosed assignment (37 CFR 1.21(h)). The assignment must be accompanied by an appropriate cover sheet (37 CFR 3.28, 3.31). \$40.00 per property

\$ 40.00

TOTAL FEES ENCLOSED =

\$ 1,300.00

Amount to be refunded: \$

charged: \$

a. ☒ credit card payment
A ~~check~~ in the amount of \$ 1,300.00 to cover the above fees is enclosed.

b. ☐ Please charge my Deposit Account No. _____ in the amount of \$ _____ to cover the above fees. A duplicate copy of this sheet is enclosed.

c. ☒ The Commissioner is hereby authorized to charge any additional fees which may be required, or credit any overpayment to Deposit Account No. 01-2135. A duplicate copy of this sheet is enclosed.

NOTE: Where an appropriate time limit under 37 CFR 1.494 or 1.495 has not been met, a petition to revive (37 CFR 1.137(a) or (b)) must be filed and granted to restore the application to pending status.

SEND ALL CORRESPONDENCE TO.

Antonelli, Terry, Stout & Kraus, LLP
1300 North 17th Street
Suite 1800
Arlington, VA 22209

SIGNATURE

Carl I. Brundidge

NAME

29,621

REGISTRATION NUMBER

566.39480X00

IN THE UNITED STATES PATENT AND TRADEMARK OFFICE

Applicants: T. KUSAKI, et al
 Serial No.: Not yet assigned
 Filed: January 12, 2001
 For: METHOD OF SWITCHING BUSY LINES IN MOBILE
 COMMUNICATION NETWORK
 Group: Not assigned
 Examiner: Not assigned

PRELIMINARY AMENDMENT

Assistant Commissioner for Patents
 Washington, D.C. 20231

January 12, 2001

Sir:

Prior to examination, please amend the above-identified
 application as follows.

IN THE SPECIFICATION

Please amend the specification as follows:

Page 1, line 4, delete "Technical Field" insert --
 Background of the Invention--;

line 9, delete "Background Art".

Page 5, line 17, insert --Summary of the Invention--.

Page 6, line 1, delete "Disclosure of the Invention".

Page 7, line 12, delete "NW" insert --the network (NW)--;

line 26, delete "Best Mode for Carrying Out the
 Invention" insert --Detailed Description of the Invention--.

IN THE CLAIMS

Please amend the claims as follows:

1. (Amended) A method of switching lines in a system comprising a data [MS (100)] mobile station (MS), a plurality of base transceiver systems [(200)] accommodating said data MS through radio lines [(150)], a base station controller [(300)] accommodating said plurality of base transceiver systems, and a data communication network [(1000)] connected to said base station controller, [wherein:]

wherein when said data MS, in the course of transmitting discontinuous data through a before-movement base transceiver system, which is one of said plurality of base transceiver systems, in an area formed by said before-movement base transceiver, moves to an area formed by an after-movement base transceiver system different from said before-movement base transceiver system,

wherein said base station controller:

detects a timing at which data transmission and reception are not performed with said before-movement base transceiver system; and

switches, at said timing, from a line set through said before-movement base transceiver system to a line through said after-movement base transceiver system, which is required after movement.

3. (Amended) A method of switching lines in a system comprising a data [MS (100)] mobile station (MS) a plurality of base transceiver systems [(200)] accommodating said data MS through radio lines [(150)], a base station controller [(300)] accommodating said plurality of base transceiver systems, and a data communication network [(1000)] connected to said base station controller, [wherein:]

wherein when said data MS, in the course of transmitting discontinuous data through a before-movement base transceiver system, which is one of said plurality of base transceiver systems, in an area formed by said before-movement base transceiver, moves to an area formed by a after-movement base transceiver system different from said before-movement base transceiver system,

wherein said base station controller:

detects, one by one, timings at which data from said data communication network is not received and timings at which data from said base transceiver system is not received;

obtains a timing at which data is not received both from said data communication network and said base transceiver system; and

switches, at said obtained timing, from a line set through said before-movement base transceiver system to a line through said after-movement base transceiver system, which is required after movement.

5. (Amended) A method of switching lines in a system comprising a data [MS (100)] mobile station (MS), a plurality of base transceiver systems [(200)] accommodating said data MS through radio lines [(150)], a base station controller [(300)] accommodating said plurality of base transceiver systems, and a data communication network [(1000)] connected to said base station controller, [wherein:]

wherein when said data MS, in the course of transmitting discontinuous data through a before-movement base transceiver system, which is one of said plurality of base transceiver systems, in an area formed by said before-movement base transceiver, moves to an area formed by an after-movement base transceiver system different from said before-movement base transceiver system,

wherein said base station controller:

receives downlink communication frames from said data communication network and edges if data is contained in said received-frames to detect a timing at which data is not received;

receives uplink communication frames from said base transceiver system and judges if data is contained in said received frames to detect a timing at which data is not received;

obtains a timing at which data is not received both from said data communication network and from said base transceiver system; and

switches, at said obtained timing, from a line set through said before-movement base transceiver system to a line through said after-movement base transceiver system, which is required after movement.

8. (Amended) A method of switching lines in a system comprising a data [MS (100)] mobile station (MS), a plurality of base transceiver systems [(200)] accommodating said data MS through radio lines [(150)], a base station controller [(300)] accommodating said plurality of base transceiver systems, and a data communication network [(1000)] connected to said base station controller, [wherein:]

wherein when said data MS, in the course of transmitting discontinuous data through a before-movement base transceiver system, which is one of said plurality of base transceiver systems, in an area formed by said before-movement base transceiver, moves to an area formed by an after-movement base transceiver system different from said before-movement base transceiver, system,

wherein said base station controller:

receives downlink communication frames from said data communication network and accumulates said frames in an NW-side buffer in said base station controller;

judges if data is contained in each. of all the frames accumulated in said NW-side buffer, to detect a timing at which data is not received for a certain period of time;

receives uplink communication frames from said base transceiver system and accumulates said frames in a base-transceiver-system-side buffer in said base station controller;

judges if data is contained in each of all the frames accumulated in said base-transceiver-system-side buffer, to detect a timing at which data is not received for a certain period of time;

obtains a timing at which data is not contained in both said uplink communication frames and said downlink communication frames for a certain period time; and

switches, at said obtained timing, from a line set through said before-movement base transceiver system to a line through said after-movement base transceiver system, which is required after movement.

14. (Amended) A base station controller in a system comprising a data [MS (100)] mobile station (MS), a plurality of base transceiver systems [(200)] accommodating said data MS

through radio lines [(150)], a base station controller [(300)] accommodating said plurality of base transceiver system, and a data communication network [(1000)] connected to said base station controller, said base station controller comprising:

an [NW] network (NW)-side interface part for receiving communication frames from said data communication network;

an NW-side buffer for accumulating frames received from said NW-side interface part;

a base-transceiver-system-side interface part for receiving communication frames from said base transceiver system; and

a base-transceiver-system-side buffer for accumulating frames received from said base-transceiver-system-side interface part.

15. (Amended) The base station controller according to Claim 14, further comprising:

[a] means for judging existence or nonexistence of data contained in each of the frames accumulated in said NW-side buffer and said base-transceiver-system-side buffer.

16. (Amended) The base station controller according to Claim 15, further comprising:

[a] means for identifying a frame number of each of the frames accumulated in said NW-side buffer and said base-transceiver-system-side buffer; and

[a] means for storing a result of judgement on existence or non-existence of data and a corresponding frame number, in association with each of the frames accumulated in the NW-side buffer and the base-transceiver-system-side buffer.

17. (Amended) A base station controller in a system comprising a data [MS (100)] mobile station (MS), a plurality of base transceiver systems [(200)] accommodating said data MS radio lines [(150)], a base station controller [(300)] accommodating said plurality of base transceiver systems, and a data communication network [(1000)] connected to said base station controller, said base station controller comprising:

an [NW] network (NW)-side interface part for receiving communication frames from said data communication network;

an NW-side buffer for accumulating frames received from said NW-side interface part;

a base-transceiver-system-side interface part for receiving communication frames from said base transceiver systems;

a base-transceiver-system-side buffer for accumulating frames received from said base-transceiver-system-side interface part;

[a] means for judging existence or nonexistence of data contained in each of the frames accumulated in said NW-side buffer and said base-transceiver-system-side buffer;

[a] means for identifying a frame number of each of the communication frames accumulated in said NW-side buffer and said base-transceiver-system-side buffer;

[a] means for storing said identified frame number and said judged existence or nonexistence of data, in association with a frame buffer number of each of the frames stored in the NW-side buffer and the base-transceiver-system-side buffer;

[a] means for extracting eL timing at which data is not received both from said data communication network and from said base transceiver systems, said extraction being performed based on said association in said means for storing; and

[a] means for extracting each frame number corresponding to said extracted timing.

19. (Amended) A data mobile station (MS) [MS] in a system comprising a data MS [(100)], a plurality of base transceiver systems [(200)] accommodating said data MS through

radio lines [(150)], a base station controller [(300)]
accommodating said plurality of base transceiver systems, and
a data communication network [(1000)] connected to said base
station controller, said data MS comprising:

[a] means for temporarily storing frames to be sent
to said base station controller;

[a] means for extracting a specific frame out of
said plurality of stored frames, based on information on said
specific frame indicated by said base station controller; and

[a] means for starting retransmission from said
extracted frame.

REMARKS

Entry of the above amendments prior to examination is
respectfully requested.

Please charge any shortage in fees due in connection with
the filing of this paper, or credit any overpayment of fees,
to the deposit account of Antonelli, Terry, Stout & Kraus,
LLP, Deposit Account No. 01-2135 (566.39480X00).

Respectfully submitted,

ANTONELLI, TERRY, STOUT & KRAUS, LLP



Carl I. Brundidge
Registration No. 29,621

CIB/jdc
(703) 312-6600

349800498/HT1607

Method of switching busy lines
in mobile communication network

Technical Field

- 5 The present invention relates to a method of switching lines, a mobile station (MS), and a base station controller (BSC) in a mobile communication network that can perform data communication.

Background Art

- 10 Conventionally, in a mobile communication network comprising mobile stations, base transceiver systems (BTS) (including base station controllers), mobile switching centers (MSC), and their peripheral equipment, processing called "handoff" is performed to continue a telephone conversation without causing
- 15 disconnection of the communication by switching lines in the upper level than the base transceiver systems according to movement of a mobile station. This handoff is classified into "hard handoff" and "soft handoff" based on difference in line connecting and switching procedures.

- 20 In "hard handoff", when a request for a start of handoff occurs in the course of communication, the communication is suspended for a while, and setting of line connection of the mobile station is switched from setting for a source base transceiver system (a base transceiver system that forms a radio area in which the mobile station is located
- 25 before the movement of the mobile station) to setting for a target base transceiver system (a base transceiver system that forms a radio area

in which the mobile station is located after the movement of the mobile station), and, at the same time, the target base transceiver system is activated. Then, in a node (for example, a base station controller) that accommodates both lines from the source and target
5 base transceiver systems, processing (line switching) is carried out such that the line connected to a host network for the source base transceiver system is reconnected for the target base transceiver system. Then, synchronism is established between the mobile station and the target base transceiver system, and the suspended
10 communication is resumed (conventional technique 1). The conventional technique 1 is described in "TIA/EIA/IS-634 MSC-BSC Interface for Public 800 MHz" and in "Association of Radio Industries and Businesses: RCR STD-27F Digital Automobile Telephone System".

15 In "soft handoff", when a request for a start of handoff (Soft Handoff Addition) occurs in the course of communication, a target base transceiver system is activated, and a mobile station establishes setting for realizing connection with that base transceiver system, with a plurality of lines being established at the same time between
20 the target base transceiver system and the mobile station and between the source base transceiver system and the mobile station, without suspending the busy line.

Then, in a node (for example, a base station controller) that accomodates both of the above-mentioned plurality of lines, the same
25 communication frames (or packets) received from a plurality of base transceiver systems are selectively synthesized to convert them to one

communication frame (or packet). This one communication frame obtained by the conversion is sent to a data communication network.

On the other hand, a communication frame received by the base station controller and destined for the mobile station from the data communication network is duplicated by the number of the above-mentioned plurality of lines, and transmitted to the above-mentioned plurality of lines. By the above-described processing, the mobile station and its host network are connected through a plurality of lines at the same time. This state is called a state of soft handoff.

On the other hand, when, in the state of soft handoff, release of one or more of the plurality of lines is requested (Soft Handoff Drop), a designated base transceiver system stops transmission and reception, and the mobile station stops communication with the base transceiver system in question, and continues communication utilizing the remaining lines.

Further, also with respect to upper lines from the base transceiver system in question, an unnecessary part of the lines is released when the base transceiver system stops transmission and reception. Thus, soft handoff is a method that can effectuate continuous communication without suspension (or a short break) of the communication, by repeatedly carrying out the above-described serial processing (conventional technique 2). The conventional technique 2 is described in "TIA/EIA/IS-634 MSC-BSC Interface for Public 800 MHz".

Differently from voice communication, data communication requires that transmit and reception data is transferred without error

between the end point on the transmit side and the end point on the reception side of the data (complete assurance). To this end, is generally employed a signaling system (for example, TCP) for performing confirmation of data delivery and control of retransmission between both end points.

However, the above-mentioned signaling system brings overhead information added to the intrinsic data part. Further, when there is a part of poor line quality between both end points, the data is retransmitted according to the signaling system in question. These incur tightening of traffic of the whole communication network and lowering of the data transfer rate between both end points.

When the above-mentioned data communication is realized in a mobile communication network, a wireless interval has poorer transmission quality than a wired interval, and has the narrowest bandwidth. Thus, the actual data transfer rate is defined by the data transfer rate in the wireless interval. Further, in a wireless interval of a mobile communication network, handoff occurs as a mobile station moves, as described by the above-mentioned conventional techniques.

When hard handoff described in the above-mentioned conventional technique 1 is started in the course of data communication, the line is temporarily disconnected while the line switching processing is performed in each apparatus. As a result, data missing occurs between both end points. Thus, after the end of the hand off, retransmission control is performed to retransmit the missing data, before reestablishing the data transmission and

reception. Namely, when hard handoff is started, thereafter retransmission control of the data is carried out. And, as a result, the actual data transfer rate between both end points is largely lowered.

5 On the other hand, even when there arises soft handoff described in the above-mentioned conventional technique 2 in the course of data communication in the same network, data missing does not occur since temporary disconnection of the line does not happen as in the case of hard handoff. However, at the time of handoff, a
10 plurality of handoff lines are established. Accordingly, one active session of data communication uses a plurality of lines, although a limited number of lines are set in advance for the network as a whole. Thus, the number of data communications that can be established at the same time is decreased. Further, in the case of packet
15 communication, bandwidth per each data communication is decreased, and accordingly, the actual data transfer rate is lowered.

 An object of the present invention is to provide a line switching method, a mobile station, and a base station controller that can perform handoff in the course of data communication in a mobile
20 communication network without lowering the data transfer rate.

 Another object of the present invention is to provide a line switching method, a mobile station, and a base station controller that can perform handoff in the course of data communication in a mobile communication network without lowering the number of data
25 communications capable of establishing at the same time.

Disclosure of the Invention

According to the present invention, for attaining the above objects, in a mobile communication system comprising a data terminal (data MS), base transceiver systems (BTS), a base station controller (BSC), a data communication network, and lines for connecting the above-mentioned elements with each other, the BSC, during activation of data communication, temporarily accumulates frames received from the connected BTS and data communication network into a frame buffer, judges if information is contained in each of a plurality of frames accumulated in the frame buffer, and stores the results of judgment into a frame information control table formed in a memory inside the BSC. On the other hand, during activation of data communication, the data MS stores frames received from connected BTSs in a frame memory at any time. When the data MS receives a new frame, contents of the oldest frame is deleted to store contents of the new frame.

When handoff (hereinafter, may be simply referred to as HO) is started, the BSC extracts a timing in which frames without containing information continue longer than the time required for the handoff- from the above-mentioned frame information control table. The extracted timing becomes the timing at which the handoff is performed. A CPU has a means for instructing a switch to perform line switching from a source line to a target line at that timing. On the other hand, a signal processing part makes handoff start timing information be included in a signal directed to the MS, and that signal is transmitted to the MS through the BTS. The data MS, which

receives that signal by a signal processing part, has a means for detecting the handoff start timing contained in that signal, a means for detecting the first of the frames that are stored in the frame memory and to be sent at that timing, and a means for starting
5 retransmission from that frame at the same time with that timing.

Brief Description of Drawings

Fig. 1 is a block diagram showing a mobile communication network to which the present invention is applied;

10 Fig. 2 is a block diagram showing the inner structure of a BSC;

Fig. 3 is a diagram showing a state of accumulation of frames in a frame buffer adapted for a line on the side of NW;

Fig. 4 is a diagram showing a state of accumulation of frames in a frame buffer adapted for a line on the side of BTS;

15 Fig. 5 is a block diagram showing the inner structure of a data MS;

Fig. 6 is a diagram showing a state of storage and accumulation of frames in an MS frame memory;

20 Fig. 7 is a diagram showing a signal sequence at the time of handoff-between MS - BTS - BSC;

Fig. 8 is a diagram showing relation between handoff timing and information vacancy timing; and

Fig. 9 shows a configuration of a frame information control table inside the BSC.

25

Best Mode for Carrying Out the Invention

Now, embodiments of the present invention will be described referring to the figures.

Fig. 1 shows an outlined configuration of a communication network system to which the present invention is applied.

5 This network comprises a data MS (mobile station) 100, a BTS (base transceiver system) 200, a BSC (base station controller) 300, and a data communication network 1000. Further, the above-mentioned elements are connected with each other through a radio line 150, a BTS - BSC line 250, or a BSC - data communication network line 400. When the data MS 100 is in the course of communication with another data communication apparatus through the data communication network 1000, data is transferred through the data MS 100, the radio line 150, the BTS 200, the BTS - BSC line 250, the BSC 300, the BSC - data communication network line 400, and the data communication network 1000. Here, the direction in the case that the data is transferred from the data MS 100 toward the data communication network 1000 is called the uplink, and the direction in the case that the data is transferred from the data communication network 1000 toward the data MS 100 is called the downlink.

10
15
20

When the MS 100 moves while connected with the BST 200 through the radio line 150 and reaches an area in which a radio line with the BTS 200A can be established, then the BSC 300 switches lines from the BTS - BSC line 250 to BTS - BSC line 250A at a timing when there is no data to be sent or received. By that operation, the communication is continued using a new channel (after-handoff data

25

transmission and reception path 500A) that passes through the data MS 100, the radio line 150A, the BTS 200A, the BTS - BSC line 250A, the BSC 300, the BSC - data communication network line 400, and the data communication network 1000. On the other hand, the
 5 channel (before-handoff data transmission and reception path 500) through which the communication has been performed is disconnected and released at the part of the radio line 150 and the BTS - BSC line 250. This operational processing is called "handoff", and, by repeating this operation, data missing does not occur even if the data
 10 MS 100 moves in the course of data communication, high throughput is ensured, and the communication is continued.

Fig. 2 shows an outline of the inner structure of the BSC 300.

The BSC 300 comprises: a BTS-side interface part 301 that accommodates the BTS - BSC line 250; an NW-side interface part 302
 15 that accommodates the BSC - data communication network line 400; a switch 303 for performing switching between the above-mentioned lines 250 and 400; a signal processing part 304 for analyzing and generating control signals on both BTS- and NW-side interfaces; a CPU 305 for performing control processing for each element inside the
 20 BSC; a memory 306 for storing control information and a program for the above-mentioned control processing; a control signal bus 307 used for sending and receiving the above-mentioned control signals between the elements; a buffer 310 adapted for a BTS-side line, which temporarily accumulates data frames received through the BTS - BSC
 25 line 250; and a buffer 320 adapted for an NW-side line, which temporarily accumulates data frames received through the BSC -

data communication network line 400.

A data frame received by the BTS-side interface part 301 through the BTS – BSC line 250 is sent to the buffer 310 adapted for the BTS-side line prepared correspondingly to each line, accumulated temporarily in that buffer, and sent to the switch 303 in FIFO order. At this time, the buffer 310 adapted for the BTS-side line accumulates a given number of frames, and judges if data is contained in each of the above-mentioned frames. The judgment result is sent to a frame information control table 350 (see Fig. 9) in the memory 306 through the control signal bus 307, and stored into the above-mentioned table. On the other hand, similarly to the BTS side, also a data frame received by the NW-side interface part 302 through the BSC – data communication network line 400 is temporarily accumulated in the buffer 320 adapted for the NW-side line, and, in that buffer 320, it is judged if data is contained or not. The judgment result is stored into the frame information control table 350. The information in the frame information control table 350 is updated every time a frame is received by the buffer 310 or 320.

In the BSC 300 carrying out the above-described operation, when a handoff request is made by the data MS 100, the BTS 200, the data network 1000, or the BSC 300 itself, that handoff request is received by the signal processing part 304 for a while. When the handoff request is recognized, a handoff program stored in the memory 306 is activated on the CPU to start the handoff processing. First, the handoff processing searches a part of the frame information control table 350 in which, out of the received frames on the BTS side

and on the NW side, frames without containing data exist consecutively for more than a period of time required for the handoff processing. When such a part is detected, a timing from a start to an end of sending the frames in that part from the buffers 310 and 320 is
 5 calculated. And, a signal indicating line switching within that timing is sent to the switch 303 through the control signal bus 307. Further, it is informed to the MS by means of the control signal processing part 304 and through the BTS that line switching, i.e. handoff, is to be carried out in that timing. Then, when the switch
 10 303 switches the lines in that timing, the handoff processing is finished.

Fig. 3 shows a state of accumulation of frames in the frame buffer 320 adapted for a line on the side of NW.

The NW-side frame buffer 320 receives data frames one by one
 15 through the BSC - data communication network line 400. The accumulated data frame 10 are accumulated in turn from the frame buffer number #1 to the number #n. A frame is sent from the frame buffer #1 to the switch 303, and, at the same time, the buffer number of each accumulated frame is changed by -1. A new frame received
 20 from the data communication network 1000 is accumulated at #n. With respect to each of the accumulated frames, it is judged if that frame contains information or not (when information is contained, it is judged as "information present", and otherwise, it is judged as "no information found"). After the judgment, one set of frame
 25 information is defined by a combination of a frame number specific to the judged frame, existence or nonexistence of information contained

in that frame, and a frame buffer number at which that frame is accumulated. Then, n sets of frame information relating to all the frames in accumulation in the frame buffer 320 adapted for a line on the NW side are sent to the memory 306 through the control signal
 5 bus 307 whenever the accumulated frames in the frame buffer 320 are updated. The sent information is stored in the frame information control table 350.

Fig. 4 shows a state of accumulation of frames in the frame buffer 310 adapted for a line on the side of BTS.

10 The BTS-side frame buffer 310 receives a data frame 11 one by one through the BTS - BSC line 250 and accumulates received frames in turn from the frame buffer number #1 to the number #n. The accumulated frame is sent from the frame buffer #1 to the switch 303, and, at the same time, the buffer number of each accumulated frame
 15 is changed by -1. A new frame received from the BTS is accumulated at #n. With respect to each of the accumulated frames, it is judged if that frame contains information or not (when information is contained, it is judged as "information present", and otherwise, it is judged as "no information found"). After the judgment, one set of
 20 frame information is defined by a combination of a frame number specific to the judged frame, existence or nonexistence of information contained in that frame, and a frame buffer number at which that frame is accumulated. Then, n sets of frame information relating to all the frames in accumulation in the frame buffer 310 adapted for a
 25 line on the BTS side are sent to the memory 306 through the control signal bus 307 whenever the accumulated frames in the frame buffer

310 are updated. The sent information is stored in the frame information control table 350.

Fig. 5 shows an outline of the inner structure of the data MS 100.

5 The data MS 100 comprises: an antenna 101 and a transmitter-receiver 102 for performing radio transmission and reception to and from a BTS; a radio interface part 103 that accommodates the radio link 150; a data-terminal-side interface part 105 for realizing connection with a data terminal; a signal processing
10 part 107 for analyzing and generating control signals on both BTS- and data-terminal-side interfaces; a CPU 106 for performing control processing for each element inside the data MS; a memory 108 for storing control information and a program for the above-mentioned control processing; a control signal bus 109 used for sending and
15 receiving the above-mentioned control signals between the elements; and an MS frame memory 104 for temporarily storing data frames sent through the radio link 150.

A data frame 11 received by the data-terminal-side interface part 105 is sent to the MS frame memory 104. When that frame
20 information is stored in the frame memory 104, that frame is sent to the radio interface part 103, and is sent to the BTS 200 through the transmitter-receiver 102 and the antenna 101. The MS frame memory 104 stores p (p : integer) frames at any time, and, when a new frame is received, contents of the oldest frame are erased to store the
25 contents of the new frame. Further, when the signal control part 107 receives a signal indicating handoff, which includes handoff timing

information, from the side of the BTS through the antenna 101, the transmitter-receiver 102, the radio interface part 103, and the control signal bus 109, then, based on the handoff timing information, the CPU 106 calculates the specific number of the frame that will passing
 5 the switch 303 just after the BSC switches lines, and instructs the MS frame memory 104 to perform retransmission from the frame having the same number as the above-mentioned specific number of the frame. By this instruction, the MS frame 104 starts retransmission from the frame having that frame number.

10 On the other hand, a data frame 10 sent from the BTS 200 is received through the antenna 101, the transmitter-receiver 102, and the radio interface part 103, and sent to the data terminal side through the data-terminal-side interface 105 without being stored in the frame memory 104.

15 Fig. 6 shows a state of storage and accumulation of frames in the MS frame memory 104.

Data frames 11 received from the data terminal are stored into the frame buffer from frame buffer number #1 through #p in turn. Frames are sent to the switch 303 of the BSC 300 from the frame
 20 whose frame buffer number is indicated by the CPU 106, and the buffer number of the accumulated frames is changed by -1.

On the other hand, separately from the MS frame buffer, the data MS is provided with a reception buffer required for receiving frames from a BTS. This reception buffer has essentially no relation
 25 to the processing operation of the present invention, and therefore is not shown in the figure.

Fig. 7 shows an outline of a signal sequence between MS – BTS – BSC from a start to an end of handoff.

When the BSC 300 decides to perform handoff (HO) in the course of communication with the data network through the data MS 100 – source BTS 200 – BSC 300 (701), the BSC 300 starts to search the frame information control table 350 stored in the memory 306 within the BSC 300 for information vacancy timing that is longer than the time required for the handoff (702). When that timing is found, the timing is decided as handoff timing (703). Next, the BSC puts the decided handoff timing information (the first and last specific numbers of the frames in successive information vacancy frames) and the information on the BTS that is the target of the handoff (target line information) into a handoff information notification signal 705, and sends the signal to the data MS 100. On receiving that signal, the data MS 100 switches the lines by switching setting of the transmitter-receiver based on the handoff timing information, and by starting retransmission from the frame at the timing corresponding to the handoff timing of the MS frame memory (707). On the other hand, also the BSC 300 switches the lines at the handoff timing that it itself-decided (706). After the end of the above operation, the data communication is restarted between the MS 100 – target BTS 200A – BSC 300 – data communication network 1000.

Fig. 8 shows relation between the handoff timing and the information vacancy timing.

With respect to frames accumulated in the frame buffer adapted for an NW-side line and in the frame buffer adapted for a

BTS-side line,

when the following conditions are satisfied:

(1) there are parts each consisting of successive frames containing no data (information vacancy timings).

5 (2) the information vacancy timings of both buffers overlap, and

(3) the overlap timing is longer than the time required for the handoff,

then, this overlap timing becomes "handoff timing".

10 In the case that the above-mentioned "handoff timing" does not exist, the following processing is carried out to generate a "handoff timing" forcibly.

(1) First, there will be described a case where both the frame buffer 320 adapted for an NW-side line and the frame buffer 310 adapted for a BTS-side line do not have a part successively containing no data. Received frames are transferred from the frame buffer 320 adapted for a line on the NW side and the frame buffer 310 adapted for a line on the BTS side to NW-side and BTS-side frame buffers (not shown) provided, in the BTS 300, separately from each other, to
15 forcibly- generate parts each consisting of successive frames containing no data. At that time, the processing is performed such
20 that both the NW and BTS sides have the same timing.

(2) Next, there will be described a case where the frame buffer 320 adapted for a line on the NW side has a part successively
25 containing no data, while the frame buffer 310 adapted for a line on the BTS side does not have such a part.

In this case, in conformity with the information vacancy timing that exists in the frame buffer 320 adapted for a line on the NW side, frames are transferred from the frame buffer 310 adapted for a line on the BTS side to the above-mentioned separately-provided
 5 frame buffer such that information vacancy timing is generated in the frame buffer 310 adapted for a line on the BTS side.

(3) Last, there will be described a case where the frame buffer 310 adapted for a line on the BTS side has a part successively containing no data, while the frame buffer 320 adapted for a line on
 10 the NW side does not have such a part.

In this case, in conformity with the information vacancy timing that exists in the frame buffer 310 adapted for a line on the BTS side, frames are transferred from the frame buffer 320 adapted for a line on the NW side to the above-mentioned separately-provided
 15 frame buffer such that information vacancy timing is generated in the frame buffer 320 adapted for a line on the NW side.

The processing of the above cases (1) through (3) is carried out by the CPU 305 according to the program in the memory 306.

It goes without saying that, in any of the above cases (1)
 20 through- (3), the forcibly-generated information timing or timings make the overlap timing longer than the time required for the handoff.

Further, in the cases of the above (1) and (2), in order to forcibly generate the information vacancy timing in the frame buffer
 25 310 adapted for a line on the BTS side, the data MS or BTS may be controlled to inhibit transfer.

According to the above-described operation, handoff timing can be forcibly generated by the BSC 300.

Fig. 9 shows a state of information control in the frame information control table 350 inside the BSC 300.

5 In the table 350, when n sets of frame information (each consisting of a frame specific number, existence or nonexistence of information contained in the frame, and a frame buffer number at which the frame is accumulated) sent from the frame buffer 320 adapted for a line on the NW side and the frame buffer 310 adapted
10 for a line on the BTS side are received, a frame buffer number is used as a key to search the same number in the "frame buffer number" 351 on the table 350. Then, into the corresponding "downlink frame specific number" 352 and "existence of downlink frame information" 353, are entered a frame specific number and existence or
15 nonexistence of information contained in that frame, which are sent from the frame buffer adapted for a line on the NW side. And, into the "uplink frame specific number" 354 and "existence of uplink frame information" 355, are entered a frame specific number and existence or nonexistence of information contained in that frame, which are
20 sent from the frame buffer adapted for a line on the BTS side. Next, the entry of the "existence of downlink frame information" and the entry of the "existence of uplink frame information" are compared for each line starting from the frame buffer number #n on the table 350. When both entries are "No", following values are set into the
25 "switching frame information" 356: the switching frame information value (k-th line) = the switching frame information value (k+1-th line)

+ 1 ($k=n+1$; the switching frame information value ($n+1$) = 0), and otherwise, the switching frame information value (k -th line) = 0.

The above-described write operation of the frame information into the table 350 is carried out whenever one frame is received by
5 both buffers 310 and 320.

When the processing operation of handoff is started and the handoff timing is searched, the "switching frame information" 350 of the table 350 is referred to. For example, in the case that the time required for handoff is more than three frames, a line whose value of
10 the switching frame information is 3 or more is searched. Then, the handoff timing is decided as the period between the transmission and reception timing (successive vacancy frame transmission timing) of the frame showing the maximum value among the detected switching frame information values and the transmission and reception timing
15 (successive vacancy frame transmission end timing) of the frame that appears as the first switching frame information value 1 under the above-mentioned line. The frame buffer number corresponding to the successive vacancy frame transmission timing and the frame buffer number corresponding to the successive vacancy frame
20 transmission end timing are sent to the CPU 305. Based on that timing information, the CPU 305 calculates the actual time at which the switch 303 switches the lines. At that time, the switch 303 switches from the source line to the target line. On the other hand, the handoff timing decided above is transmitted to the data MS 100 by
25 means of the signal processing part 304 through the source BTS 200. Based on that information, the data MS 100 decides frame

retransmission timing and starts the retransmission.

Industrial Applicability

In a mobile communication network to which the present
5 invention is applied, when handoff is started owing to movement of a
data terminal in the course of communication, actual data missing
does not occur although the data communication network is
temporarily disconnected. Accordingly, it is possible to realize
handoff that does not invite lowering of the data transfer rate.
10 Further, since the actual data missing can be excluded without using
the conventional soft handoff, and simultaneous use of a plurality of
lines is not necessary, the number of admitted subscribers is expected
to increase in comparison with the data communication network using
the soft handoff. Further, in the case that the present invention is
15 applied to packet data communication, traffic is not tightened since
soft handoff is not used, and accordingly, lowering of the data
transfer rate can be prevented.

WHAT IS CLAIMED IS:

1 1. A method of switching lines in a data MS (100), a plurality of
2 base transceiver systems (200) accommodating said data MS through
3 radio lines (150), a base station controller (300) accommodating said
4 plurality of base transceiver systems, and a data communication
5 network (1000) connected to said base station controller, wherein:

6 when said data MS, in the course of transmitting
7 discontinuous data through a before-movement base transceiver
8 system, which is one of said plurality of base transceiver systems, in
9 an area formed by said before-movement base transceiver, moves to
10 an area formed by an after-movement base transceiver system
11 different from said before-movement base transceiver system,

12 said base station controller:

13 detects a timing at which data transmission and reception are
14 not performed with said before-movement base transceiver system;
15 and

16 switches, at said timing, from a line set through said before-
17 movement base transceiver system to a line through said after-
18 movement base transceiver system, which is required after
19 movement.

1 2. The method of switching lines according to Claim 1, wherein:
2 said timing at which data transmission and reception are not

3 performed, which is detected by said base station controller, is
4 communicated to said data MS.

1 3. A method of switching lines in a data MS (100), a plurality of
2 base transceiver systems (200) accommodating said data MS through
3 radio lines (150), a base station controller (300) accommodating said
4 plurality of base transceiver systems, and a data communication
5 network (1000) connected to said base station controller, wherein:
6 when said data MS, in the course of transmitting
7 discontinuous data through a before-movement base transceiver
8 system, which is one of said plurality of base transceiver systems, in
9 an area formed by said before-movement base transceiver, moves to
10 an area formed by a after-movement base transceiver system different
11 from said before-movement base transceiver system,
12 said base station controller:
13 detects, one by one, timings at which data from said data
14 communication network is not received and timings at which data
15 from said base transceiver system is not received;
16 obtains a timing at which data is not received both from said
17 data communication network and said base transceiver system; and
18 switches, at said obtained timing, from a line set through said
19 before-movement base transceiver system to a line through said
20 after-movement base transceiver system, which is required after
21 movement.

1 4. The method of switching lines according to Claim 3, wherein:

2 said timing at which data is not received both from said data
3 communication network and from said base transceiver system, which
4 is detected by said base station controller, is communicated to said
5 data MS.

1 5. A method of switching lines in a data MS (100), a plurality of
2 base transceiver systems (200) accommodating said data MS through
3 radio lines (150), a base station controller (300) accommodating said
4 plurality of base transceiver systems, and a data communication
5 network (1000) connected to said base station controller, wherein:

6 when said data MS, in the course of transmitting
7 discontinuous data through a before-movement base transceiver
8 system, which is one of said plurality of base transceiver systems, in
9 an area formed by said before-movement base transceiver, moves to
10 an area formed by an after-movement base transceiver system
11 different from said before-movement base transceiver system,

12 said base station controller:

13 receives downlink communication frames from said data
14 communication network and judges if data is contained in said
15 received frames to detect a timing at which data is not received;

16 receives uplink communication frames from said base
17 transceiver system and judges if data is contained in said received
18 frames to detect a timing at which data is not received;

19 obtains a timing at which data is not received both from said
20 data communication network and from said base transceiver system;
21 and

22 switches, at said obtained timing, from a line set through said
 23 before-movement base transceiver system to a line through said
 24 after-movement base transceiver system, which is required after
 25 movement.

1 6. The method of switching lines according to Claim 5, wherein:
 2 said timing at which data is not received both from said data
 3 communication network and from said base transceiver system, which
 4 is detected by said base station controller, is communicated to said
 5 data MS.

1 7. The method of switching lines according to Claim 5, wherein:
 2 said data MS:
 3 stores, temporarily, a plurality of frames to be sent to said
 4 base transceiver system;
 5 detects a frame corresponding to said communicated timing
 6 among said plurality of frames stored temporarily in the data MS; and
 7 performs retransmission from said detected frame.

1 8. A method of switching lines in a data MS (100), a plurality of
 2 base transceiver systems (200) accommodating said data MS through
 3 radio lines (150), a base station controller (300) accommodating said
 4 plurality of base transceiver systems, and a data communication
 5 network (1000) connected to said base station controller, wherein:
 6 when said data MS, in the course of transmitting
 7 discontinuous data through a before-movement base transceiver

8 system, which is one of said plurality of base transceiver systems, in
9 an area formed by said before-movement base transceiver, moves to
10 an area formed by an after-movement base transceiver system
11 different from said before-movement base transceiver system,

12 said base station controller:

13 receives downlink communication frames from said data
14 communication network and accumulates said frames in an NW-side
15 buffer in said base station controller;

16 judges if data is contained in each of all the frames
17 accumulated in said NW-side buffer, to detect a timing at which data
18 is not received for a certain period of time;

19 receives uplink communication frames from said base
20 transceiver system and accumulates said frames in a base-
21 transceiver-system-side buffer in said base station controller;

22 judges if data is contained in each of all the frames
23 accumulated in said base-transceiver-system-side buffer, to detect a
24 timing at which data is not received for a certain period of time;

25 obtains a timing at which data is not contained in both said
26 uplink communication frames and said downlink communication
27 frames for a certain period time; and

28 switches, at said obtained timing, from a line set through said
29 before-movement base transceiver system to a line through said
30 after-movement base transceiver system, which is required after
31 movement.

1 9. The method of switching lines according to Claim 8, wherein:

2 with respect to each of the communication frames accumulated
 3 in each of said NW-side buffer and said base-transceiver-system-side
 4 buffer, a specific number of the frame and existence or nonexistence
 5 of information contained in said frame are stored into an information
 6 control table, being associated with a frame buffer number of the
 7 frame; and

8 said table is used to detect a timing at which data is not
 9 contained in both said uplink communication frames and said
 10 downlink communication frames, for a certain period of time.

1 10. The method of switching lines according to Claim 9, wherein:
 2 said timing at which data is not received, which is detected by
 3 said base station controller, is communicated to said data MS.

1 11. The method of switching lines according to Claim 10, wherein:
 2 said data MS:
 3 stores, temporarily, a plurality of frames to be sent to said
 4 base transceiver system;
 5 detects a frame number corresponding to said communicated
 6 timing among said plurality of frames stored temporarily in the data
 7 MS, said detection being carried out based on contents of said table;
 8 and
 9 performs retransmission from said detected frame.

1 12. The method of switching lines according to Claim 10, wherein:
 2 said timing communication to said data MS is carried out by

3 communicating the frame number corresponding to the timing at
4 which data is not received both from said data communication
5 network and from said base transceiver system, which is detected by
6 said base station controller.

1 13. The method of switching lines according to Claim 12, wherein:
2 said data MS stores, temporarily, a plurality of frames to be
3 sent to said base transceiver system and respective frame numbers of
4 said plurality of frames;
5 said frame number corresponding to the timing at which data
6 is not received both from said data communication network and from
7 said base transceiver system, which is detected by said base station
8 controller, is communicated to said data MS; and
9 said data MS detects a frame corresponding to said frame
10 number, which is sent at said timing, among said plurality of frames
11 temporarily stored in said data MS, and performs retransmission
12 from said detected frame.

1 14. A base station controller in a data MS (100), a plurality of
2 base transceiver systems (200) accommodating said data MS through
3 radio lines (150), a base station controller (300) accommodating said
4 plurality of base transceiver systems, and a data communication
5 network (1000) connected to said base station controller, said base
6 station controller comprising:

7 an NW-side interface part for receiving communication frames
8 from said data communication network;

9 an NW-side buffer for accumulating frames received from said
10 NW-side interface part;
11 a base-transceiver-system-side interface part for receiving
12 communication frames from said base transceiver systems; and
13 a base-transceiver-system-side buffer for accumulating frames
14 received from said base-transceiver-system-side interface part.

1 15. The base station controller according to Claim 14, further
2 comprising:

3 a means for judging existence or nonexistence of data
4 contained in each of the frames accumulated in said NW-side buffer
5 and said base-transceiver-system-side buffer.

1 16. The base station controller according to Claim 15, further
2 comprising:

3 a means for identifying a frame number of each of the frames
4 accumulated in said NW-side buffer and said base-transceiver-
5 system-side buffer; and

6 a means for storing a result of judgement on existence or
7 nonexistence of data and a corresponding frame number, -in
8 association with each of the frames accumulated in the NW-side
9 buffer and the base-transceiver-system-side buffer.

1 17. A base station controller in a data MS (100), a plurality of
2 base transceiver systems (200) accommodating said data MS through
3 radio lines (150), a base station controller (300) accommodating said

4 plurality of base transceiver systems, and a data communication
5 network (1000) connected to said base station controller, said base
6 station controller comprising:

7 an NW-side interface part for receiving communication frames
8 from said data communication network;

9 an NW-side buffer for accumulating frames received from said
10 NW-side interface part;

11 a base-transceiver-system-side interface part for receiving
12 communication frames from said base transceiver systems;

13 a base-transceiver-system-side buffer for accumulating frames
14 received from said base-transceiver-system-side interface part;

15 a means for judging existence or nonexistence of data
16 contained in each of the frames accumulated in said NW-side buffer
17 and said base-transceiver-system-side buffer;

18 a means for identifying a frame number of each of the
19 communication frames accumulated in said NW-side buffer and said
20 base-transceiver-system-side buffer;

21 a means for storing said identified frame number and said
22 judged existence or nonexistence of data, in association with a frame
23 buffer number of each of the frames stored in the NW-side buffer and
24 the base-transceiver-system-side buffer;

25 a means for extracting a timing at which data is not received
26 both from said data communication network and from said base
27 transceiver systems, said extraction being performed based on said
28 association in said means for storing; and

29 a means for extracting each frame number corresponding to

30 said extracted timing.

1 18. The base station controller according to Claim 17, further
 2 comprising a means for sending said extracted each frame number to
 3 said data MS.

1 19. A data MS in a data MS (100), a plurality of base transceiver
 2 systems (200) accommodating said data MS through radio lines (150),
 3 a base station controller (300) accommodating said plurality of base
 4 transceiver systems, and a data communication network (1000)
 5 connected to said base station controller, said data MS comprising:
 6 a means for temporarily storing frames to be sent to said base
 7 station controller;
 8 a means for extracting a specific frame out of said plurality of
 9 stored frames, based on information on said specific frame indicated
 10 by said base station controller; and
 11 a means for starting retransmission from said extracted
 12 frame.

1 20. The data MS according to Claim 19, wherein:
 2 said means for temporarily storing stores frames and frame
 3 numbers of said frames.

Abstract

A method of switching lines during data communication in a mobile communication system without lowering the data transfer rate and increasing traffic. In a mobile communication network comprising a data MS 100, a BTS 200, a BSC 300, and a data communication network 1000, when data transfer lines are switched from a before-handoff data transmission-reception path 500 to a before-handoff data transmission-reception path 500A in accordance with movement of the data MS 100, switching of busy lines is performed such that the BSC 300 detects a timing at which data is not transmitted and received, and switches the lines at that timing.

FIG. 1




FIG.2




FIG.3




FIG. 4




FIG.5




FIG.6




FIG. 7




FIG. 8




FIG.9

FRAME INFORMATION CONTROL TABLE 350

FRAME BUFFER NUMBER 351	DOWNLINK FRAME 352		UPLINK FRAME 354		SWITCHING FRAME INFORMATION 356
	SPECIFIC NUMBER	EXISTENCE OF INFORMATION 353	SPECIFIC NUMBER	EXISTENCE OF INFORMATION	
#1	#15	YES	#7	YES	0
#2	#16	YES	#8	YES	0
#3	#17	NO	#9	YES	0
#4	#18	NO	#10	NO	3
#5	#19	NO	#11	NO	2
#6	#20	NO	#12	NO	1
#7	#21	YES	#13	NO	0
⋮	⋮	⋮	⋮	⋮	⋮
#n	#m	NO	#k	NO	1

Declaration and Power of Attorney For Patent Application

特許出願宣言書及び委任状

Japanese Language Declaration

日本語宣言書

下記の氏名の発明者として、私は以下の通り宣言します。

As a below named inventor, I hereby declare that:

私の住所、私書箱、国籍は下記の私の氏名の後に記載された通りです。

My residence, post office address and citizenship are as stated next to my name.

下記の名称の発明に関して請求範囲に記載され、特許出願している発明内容について、私が最初かつ唯一の発明者（下記の氏名が一つの場合）もしくは最初かつ共同発明者であると（下記の名称が複数の場合）信じています。

I believe I am the original, first and sole inventor (if only one name is listed below) or an original, first and joint inventor (if plural names are listed below) of the subject matter which is claimed and for which a patent is sought on the invention entitled

METHOD OF SWITCHING BUSY

LINES IN MOBILE COMMUNICATION

NETWORK

上記発明の明細書（下記の欄で×印がついていない場合は、本書に添付）は、

The specification of which is attached hereto unless the following box is checked:

☐ __月__日に提出され、米国出願番号または特許協定条約国際出願番号を____ととし、
(該当する場合) _____に訂正されました。

☒ was filed on 15/July/1998
as United States Application Number or
PCT International Application Number
PCT/JP98/03178 and was amended on
_____ (if applicable).

私は、特許請求範囲を含む上記訂正後の明細書を検討し、内容を理解していることをここに表明します。

I hereby state that I have reviewed and understand the contents of the above identified specification, including the claims, as amended by any amendment referred to above.

私は、連邦規則法典第37編第1条56項に定義されるとおり、特許資格の有無について重要な情報を開示する義務があることを認めます。

I acknowledge the duty to disclose information which is material to patentability as defined in Title 37, Code of Federal Regulations, Section 1.56.

Japanese Language Declaration (日本語宣言書)

私は、米国法典第35編119条(a)-(d)項又は365条(b)項に基づき下記の、米国以外の国の少なくとも一カ国を指定している特許協力条約365(a)項に基づき国際出願、又は外国での特許出願もしくは発明者証の出願についての外国優先権をここに主張するとともに、優先権を主張している、本出願の前に出願された特許または発明者証の外国出願を以下に、枠内をマークすることで、示している。

Prior Foreign Application(s)

外国での先行出願

PCT/JP98/03178	Japan
(Number)	(Country)
(番号)	(国名)
(Number)	(Country)
(番号)	(国名)

私は、第35編米国法典119条(e)項に基づいて下記の米国特許出願規定に記載された権利をここに主張いたします。

(Application No.)	(Filing Date)
(出願番号)	(出願日)

私は、下記の米国法典第35編120条に基づいて下記の米国特許出願に記載された権利、又は米国を指定している特許協力条約365条(c)に基づき権利をここに主張します。また、本出願の各請求範囲の内容が米国法典第35編112条第1項又は特許協力条約で規定された方法で先行する米国特許出願に開示されていない限り、その先行米国出願書提出日以降で本出願書の日本国内または特許協力条約国際提出日までの期間中に入手された、連邦規則法典第37編1条56項で定義された特許資格の有無に関する重要な情報について開示義務があることを認識しています。

(Application No.)	(Filing Date)
(出願番号)	(出願日)

(Application No.)	(Filing Date)
(出願番号)	(出願日)

私は、私自身の知識に基づいて本宣言書で私が行なう表明が真実であり、かつ私の入手した情報と私の信じることに基づく表明が全て真実であると信じていること、さらに故意になされた虚偽の表明及びそれと同等の行為は米国法典第18編第1001条に基づき、罰金または拘禁、もしくはその両方により処罰されること、そしてそのような故意による虚偽の表明を行なえば、出願した、又は既に許可された特許の有効性が失われることを認識し、よってここに上記のごとく宣誓を致します。

I hereby claim foreign priority under Title 35, United States Code, Section 119 (a)-(d) or 365(b) of any foreign application(s) for patent or inventor's certificate, or 365(a) of any PCT international application which designated at least one country other than the United States, listed below and have also identified below, by checking the box, any foreign application for patent or inventor's certificate, or PCT International application having a filing date before that of the application on which priority is claimed.

Priority Not Claimed

優先権主張なし

15/July/1998	
(Day/Month/Year Filed)	<input type="checkbox"/>
(出願年月日)	

(Day/Month/Year Filed)	<input type="checkbox"/>
(出願年月日)	

I hereby claim the benefit under Title 35, United States Code, Section 119(e) of any United States provisional application(s) listed below.

(Application No.)	(Filing Date)
(出願番号)	(出願日)

I hereby claim the benefit under Title 35, United States Code, Section 120 of any United States application(s), or 365(c) of any PCT international application designating the United States, listed below and, insofar as the subject matter of each of the claims of this application is not disclosed in the prior United States or PCT International application in the manner provided by the first paragraph of Title 35, United States Code Section 112, I acknowledge the duty to disclose information which is material to patentability as defined in Title 37, Code of Federal Regulations, Section 1.56 which became available between the filing date of the prior application and the national or PCT international filing date of application.

(Status: Patented, Pending, Abandoned)	
(現況: 特許許可済、係属中、放棄済)	

(Status: Patented, Pending, Abandoned)	
(現況: 特許許可済、係属中、放棄済)	

I hereby declare that all statements made herein of my own knowledge are true and that all statements made on information and belief are believed to be true; and further that these statements were made with the knowledge that willful false statements and the like so made are punishable by fine or imprisonment, or both, under Section 1001 of Title 18 of the United States Code and that such willful false statements may jeopardize the validity of the application or any patent issued thereon.

Japanese Language Declaration (日本語宣言書)

委任状： 私は下記の発明者として、本出願に関する一切の手続きを米特許商標局に対して遂行する弁理士または代理人として、下記の者を指名いたします。(弁護士、または代理人の氏名及び登録番号を明記のこと)

POWER OF ATTORNEY: As a named inventor, I hereby appoint the following attorney(s) and/or agent(s) to prosecute this application and transact all business in the Patent and Trademark Office connected therewith (list name and registration number)

Donald R. Antonelli, Reg. No. 20,296; David T. Terry, Reg. No. 20,178; Melvin Kraus, Reg. No. 22,466; William I. Solomon, Reg. No. 28,565; Gregory E. Montone, Reg. No. 28,141; Ronald J. Shore, Reg. No. 28,577; Donald E. Stout, Reg. No. 26,422; Alan E. Schiavelli, Reg. No. 32,087; James N. Dresser, Reg. No. 22,973 and Carl I. Brundidge, Reg. No. 29,621

書類送付先

Send Correspondence to:

Antonelli, Terry, Stout & Kraus, LLP
Suite 1800
1300 North Seventeenth Street
Arlington, Virginia 22209

直接電話連絡先：(氏名及び電話番号)

Direct Telephone Calls to: (name and telephone number)

Telephone: (703) 312-6600
Fax: (703) 312-6666

唯一または第一発明者	1-00	Full name of sole or first inventor Tsutomu KUSAKI
発明者の署名	日付	Inventor's signature Date
住所		Residence Yokohama, Japan
国籍		Citizenship Japan
私書箱		Post Office Address c/o Hitachi, Ltd., Intellectual Property Group New Marunouchi Bldg. 5-1, Marunouchi 1-chome, Chiyoda-ku, Tokyo 100-8220, Japan

(第二以降の共同発明者についても同様に記載し、署名をすること)

(Supply similar information and signature for second and subsequent joint inventors.)

Under the Paperwork Reduction Act of 1995, no persons are required to respond to a collection of information unless it displays a valid OMB control number.

第二共同発明者		2-00		Full name of second joint inventor, if any	
第二共同発明者の署名		日付		Koji HIRAYAMA	
				Second inventor's signature	Date
				Koji Hirayama	10/27/2000
住所		Residence			
		Yokohama, Japan JPX			
国籍		Citizenship			
		Japan			
私書箱		Post Office Address			
		c/o Hitachi, Ltd., Intellectual Property Group New Marunouchi Bldg. 5-1, Marunouchi 1-chome, Chiyoda-ku, Tokyo 100-8220, Japan			
第三共同発明者		3-00		Full name of third joint inventor, if any	
第三共同発明者の署名		日付		Keisuke SHIRAI	
				Third inventor's signature	Date
				Keisuke Shirai	10/31/2000
住所		Residence			
		Yokohama, Japan JPX			
国籍		Citizenship			
		Japan			
私書箱		Post Office Address			
		c/o Hitachi, Ltd., Intellectual Property Group New Marunouchi Bldg. 5-1, Marunouchi 1-chome, Chiyoda-ku, Tokyo 100-8220, Japan			
第四共同発明者		Full name of fourth joint inventor, if any			
第四共同発明者の署名		日付		Fourth inventor's signature	
				Date	
住所		Residence			
		Citizenship			
国籍		Post Office Address			
私書箱		Full name of fifth joint inventor, if any			
第五共同発明者		Full name of fifth joint inventor, if any			
第五共同発明者の署名		日付		Fifth inventor's signature	
				Date	
住所		Residence			
国籍		Citizenship			
私書箱		Post Office Address			

(第六以降の共同発明者についても同様に記載し、署名をすること)
(Supply similar information and signature for sixth and subsequent joint inventors.)



Under the Paperwork Reduction Act of 1995, no persons are required to respond to a collection of information unless it displays a valid OMB control number.

CHANGE OF CORRESPONDENCE ADDRESS <i>Application</i> Address to: Assistant Commissioner for Patents Washington, D.C. 20231	Application Number	09/743631
	Filing Date	JANUARY 12, 2001
	First Named Inventor	KUSAKI, ET AL.
	Group Art Unit	
	Examiner Name	
	Attorney Docket Number	566.39480X00

Please change the Correspondence Address for the above-identified application to:



Customer Number

020457

Type Customer Number here



020457

PATENT TRADEMARK OFFICE

OR

Firm or
Individual Name

Address

Address

City

State

ZIP

Country

Telephone

Fax

This form cannot be used to change the data associated with a Customer Number. To change the data associated with an existing Customer Number use "Request for Customer Number Data Change" (PTO/SB/124).

I am the :



Applicant.

Assignee of record of the entire interest.
Certificate under 37 CFR 3.73(b) is enclosed.

Attorney or agent of record .

Typed or Printed Name	Carl I. Brundidge	Registration NO.	29,621
Signature			
Date	January 12, 2001		

Burden Hour Statement: This form is estimated to take 0.2 hours to complete. Time will vary depending upon the needs of the individual case. Any comments on the amount of time you are required to complete this form should be sent to the Chief Information Officer, Patent and Trademark Office, Washington, DC 20231. DO NOT SEND FEES OR COMPLETED FORMS TO THIS ADDRESS. SEND TO: Assistant Commissioner for Patents, Washington, DC 20231.